



UQ-POWER

Energy Equipment

UQ POWER RENTAL SERIES GENERATORS

UQ-70: Standby Rating: 70kVA / 56kW Prime Rating: 63 kVA / 51 kW

UQ-80: Standby Rating: 81 kVA / 65kW Prime Rating: 73kVA / 59kW



LARGE CAPACITY FUEL CELL



CUSTOMER CONNECTION PANEL



REAR CONTROL PANEL WITH MLCB



EASY ACCESS FOR MAINTENANCE

GENERATOR FEATURES

- Perkins Tier 3/Flex engine
- Brushless Alternator with PMG motor starting performance
- Digital engine generator controller
- Multi voltage switch with utility power in both 120/240 and 120/208 modes
- Buss bar, Cam-Lok, and utility outlets for customer connections
- 10 gauge, powder coated, lockable, sound attenuated enclosure
- Large capacity dual containment fuel cell with environmental containment basin
- Single point lift
- Available with or without trailer
- Custom branding options available

PERKINS DIESEL ENGINES

- Heavy Duty, 4-cycle, direct Injection, turbo-charged diesel engine for maximum reliability
- EPA FLEX Products (TIER 3 Technology)
- JP-8Compatible
- Fuel efficient
- Heavy duty/Industrial construction
- Electronic fuel system and governor system. Maintains isochronous frequency control from no load to full load

ALTERNATORS

- 105° C PMG alternators for better motor starting

ENGINE/GENERATOR CONTROLS

- Deep Sea Digital Controller Model #7310

Model	Voltages	Standby kVA/KW	Prime kVA/KW	Engine model	Alternator
UQ-70	120/208/240/277/480	70kva/ 56KW	63kVA / 51KW	1104D-44TG1	SLG224D
UQ-80	120/208/240/277/480	81kVA / 65KW	73kVA / 59KW	1104D-E44TG1	SLG224E



**3 POSITION VOLTAGE
SELECTOR SWITCH**

Engine Data	UQ-70	UQ-80
Engine Mfg	PERKINS	PERKINS
Model Number	1104D-44TG1	1104D-E44TG1
Fuel	Diesel	Diesel
Gross rated output HP	86 (64kw)	129 (96kw)
Oil Capacity Gallons (liters)	2.1 (8)	2.1 (8)
Emissions certification	Tier 3 / Flex	Tier 3 / Flex
Fuel tank capacity - Gallons	124 (469)	124 (469)
Fuel consumption at prime rating	4.3 gph	4.9 gph
25% load Gph	1.3	1.6
50% load	2.1	2.8
75% load	3.3	3.9
100% load	4.3	4.9




**LOCKABLE EXTERNAL FUEL
FILL**

Alternator data	UQ-70	UQ-80
Alternator Model	SLG224D	SLG224E
Available voltages	120/208/240/480	120/208/240/480
277/480v 3 phase - amps	77	88
120/208v 3 phase- amps	175	203
120/240 3 phase –amps	153	177
120/240 1 phase –amps	141 (Zig Zag)	163 (Zig Zag)
3 phase voltage selection	120/208—139/240—277/480	120/208—139/240—277/480
1 phase voltage selection	120/240	120/240



**CUSTOMER CONNECTION
CAM-LOK STANDARD**

Enclosure data	UQ-70	UQ-80
Length - Enclosure only	111"	111"
Width	43"	43"
Height	64"	64"
Weight-dry	4400LBS	4400 LBS
Length with trailer	192	192
Width with trailer	76	76
Height with trailer	82	82
Weight with trailer	6050 LBS	6050 LBS
Weight with trailer ready to run	7170 LBS	7170 LBS



HEAVY DUTY TRAILER

Sound dBA level @ 23 ft.	69dBA	69dBA
--------------------------	-------	-------

Distributed By:

UQ-POWER
Energy Equipment

(800) 760-9598
(209) 227-6586 Fax
P.O. Box 32230
Stockton, CA 95213



Turnkey Industries is an expert in the field of purchasing and selling pre-owned industrial generators. We offer many different brands, sizes, and capacities of generators. We fulfill orders across the country and beyond, and our elaborate preparatory processes ensure that our equipment is ready for immediate usage on arrival.

[See All Inventory](#)



**Immediate
Availability**



**Worldwide
Delivery**



**Low Hour
Generator Sets**

Contact Us



sales@turnkey-industries.com



713-823-0890



Turnkey Industries, LLC
P.O. Box 3876 Humble, TX 77347

